














# Produktübersicht SAUER-Hochleistungs-Zahnradpumpen und Motoren

Typenübersicht		Baugröße geometrisches Fördervol. V <sub>g</sub> [cm <sup>3</sup> ]	Maximaler Betriebs- druck bar	Maximale Drehzahl [min <sup>-1</sup> ]	Typenübersicht für SAE-Ausführung		
PA*		TFP 50/0,25 •	0,25	200	10.000		
		TFP 50/0,45	0,45	200	10.000		
		TFP 50/0,57 •	0,57	200	10.000		
		TFP 50/0,76 •	0,76	200	6.000		
		TFP 50/1,27	1,27	200	6.000		
PB*		TFP 100/1,2	1,2	210	6.000	TFP 100/1,2	SAE „AA“ 
		TFP 100/1,7 •	1,7	210	6.000	TFP 100/1,7	
		TFP 100/2,2 •	2,2	210	6.000	TFP 100/2,2 •	
		TFP/TFM 100/2,6 •	2,6	210	6.000	TFP 100/2,6	
		TFP/TFM 100/3,2 •	3,2	210	6.000	TFP 100/3,2	
		TFP/TFM 100/3,8 •	3,8	210	6.000	TFP 100/3,8	
		TFP/TFM 100/4,3 •	4,3	210	4.000	TFP 100/4,3 •	
		TFP 100/7,8	7,8	180	4.000	TFP 100/7,8 •	
		PC*		TFP 200/ 6 •	6	250	
TFP/TFM 200/ 8,5 •	8,5			250	4.000		
TFP/TFM 200/11 •	11			250	4.000		
TFP/TFM 200/14,5 •	14,5			225	4.000		
TFP/TFM 200/17 •	17			210	4.000		
TFP/TFM 200/19,5 •	19,5			180	3.500		
TFP/TFM 200/26,5	26,5			140	3.500		
PK*		TKP 200/ 4	4	210	4.000		
		TKP 200/ 6 •	6	210	4.000		
		TKP 200/ 8,5 ▲•	8,5	210	4.000		
		TKP 200/11 ▲•	11	210	4.000		
		TKP 200/14,5 ▲•	14,5	210	4.000		
		TKP 200/17 ▲•	17	210	4.000		
		TKP 200/19,5 •	19,5	180	3.500		
		TKP 200/22,5	22,5	160	3.500		
		4	250	4.000	TKP 4-26/ 4 •	SAE „A“ 	
		6,2	250	4.000	TKP 4-26/ 6,2 •		
		8,4	250	4.000	TKP 4-26/ 8,4 •		
		11	250	4.000	TKP 4-26/11 •		
		14,3	225	4.000	TKP 4-26/14,3 •		
		16,5	210	4.000	TKP 4-26/16,5 •		
		19,2	180	4.000	TKP 4-26/19,2 •		
		25	140	3.000	TKP 4-26/25		
PJ*		TSP 4-26/ 4 •	4	210	4.000		
		TSP 4-26/ 6,2	6,2	210	4.000		
		TSP 4-26/ 8,4 •	8,4	210	4.000		
		TSP 4-26/11 •	11	210	3.500		
		TSP 4-26/14,3 •	14,3	210	3.500		
		TSP 4-26/16,5	16,5	190	3.500		
PE*		TAP/TAM 22-90/22	22	300	3.000	TAP 22-90/22 •	SAE „B“ 
		TAP/TAM 22-90/26,5	26,5	300	3.000	TAP 22-90/26,5 •	
		TAP/TAM 22-90/33,5 •	33,5	300	3.000	TAP 22-90/33,5 •	
		TAP/TAM 22-90/38 •	38	300	3.000	TAP 22-90/38 •	
		TAP/TAM 22-90/44 •	44	260	3.000	TAP 22-90/44 •	
		TAP/TAM 22-90/55 •	55	225	3.000	TAP 22-90/55 •	
		TAP/TAM 22-90/63 •	63	210	3.000	TAP 22-90/63 •	
		TAP/TAM 22-90/75	75	180	3.000	TAP 22-90/75	
		TAP/TAM 22-90/90	90	150	2.500	TAP 22-90/90	
PF*		TAP 60-200/ 60	60	280	3.000	TAP 60-200/ 60	SAE „C“ 
		TAP 60-200/ 85	85	280	3.000	TAP 60-200/ 85	
		TAP 60-200/106 •	106	235	2.500	TAP 60-200/106	
		TAP 60-200/130 •	130	220	2.500	TAP 60-200/130	
		TAP 60-200/148 •	148	210	2.400	TAP 60-200/148	
		TAP 60-200/180	180	170	2.400	TAP 60-200/180	
		TAP 60-200/200	200	150	2.400	TAP 60-200/200	

• Lagerhaltige Vorzugsbaugrößen, Einzelpumpen.

▲ Lagerhaltige Vorzugsbaugrößen, Doppelpumpen

\* Kurzbuchstaben für Doppelpumpenstufen, z. B. TFP 100+ TFP 100 = PBB

Technische Änderungen vorbehalten.